

**PART R34****SURFACE CHARACTERISTICS - SPRAY SEALS****CONTENTS**

1. GENERAL
2. PROPERTIES OF THE SURFACE
3. ACCEPTANCE CRITERIA
4. RECTIFICATION WORK
5. TEST PROCEDURES
6. PAYMENT

**1. GENERAL**

- .1 This Part applies to pavements with sprayed bituminous surfacing or resurfacing and specifies the surface characteristics that the Contractor must achieve and the requirements for the measurement and reporting of these characteristics.
- .2 This Part only applies to the following characteristics:
  - (a) aggregate removal;
  - (b) aggregate retention; and
  - (c) surface texture.
- .3 For any requirements relating to surface roughness, refer to Part R35 "Surface Characteristics – Roughness".
- .4 Compliance with requirements specified elsewhere in this Specification does not relieve the Contractor of the obligation to comply with the requirements of this Part.
- .5 The definitions in "AUSTROADS Guide to Selection of Road Surfacing" apply to this Contract.

**2. PROPERTIES OF THE SURFACE**

- .1 The Contractor must construct a surface which:
  - (a) has minimal loose aggregate to reduce the potential for accidents and vehicle damage;
  - (b) retains aggregate after application to provide skid resistance and prevent water from entering and weakening the pavement; and
  - (c) has a surface texture to optimise contact between the road surface and tyres and provide a skid resistant surface.

**3. ACCEPTANCE CRITERIA**

- .1 Seals and primerseals must comply with the acceptance criteria for Removal of Loose Aggregate, Retention of Aggregate and Surface Texture specified in Part R26 "Application of Spray Sealing".
- .2 Further to Clause G20.2 "Definitions", a lot must be the lesser of 500 m or a homogenous spray run. Aprons, turning lanes, and other minor spray work must be deemed as separate lots.
- .3 Where the work is a reseal, the Contractor may undertake testing to verify information supplied by the Principal prior to commencement of work.

**4. RECTIFICATION WORK**

- .1 If there is a non-compliance with the requirements of this part, the Contractor must promptly undertake rectification of the non-compliance. The Contractor must provide the following information:
  - (a) date non-conforming work was identified;
  - (b) date rectification work was undertaken;
  - (c) full details and description of rectification work;
  - (d) verification records.

- .2 If the road is becoming unsafe for road users, rectification must be carried out within 24 hours of identification of problem. This includes the situation where bleeding bituminous material could be picked up by traffic or there is excessive loose stone on the surface (as determined in accordance with Part R26 "Application of Spray Sealing").
- .3 If conditions are gradually deteriorating, rectification must be carried out within 30 days of identification of problem.

## 5. TEST PROCEDURES

- .1 The Contractor must use the following test procedures (refer [http://www.dpti.sa.gov.au/contractor\\_documents](http://www.dpti.sa.gov.au/contractor_documents)) to verify conformance with the Specification:

TEST	TEST PROCEDURE
Determination of Average Texture Depth of a Pavement Surface by the Sand Patch Method	TP 346

## 6. PAYMENT

- .1 Payment will only be made for segments or lots meeting the Acceptance Criteria in accordance with this Clause.
- .2 The Payment due must be the sum of payments for conforming lots calculated in accordance with the following formulae:

$$\text{At completion of work: } P = 0.5 \times P_j \times CI$$

$$3 \text{ months after completion of the work: } P = 0.5 \times P_j \times CI$$

where:

$P$  = Payment Due

$$CI = \frac{\text{Cumulative area of conforming lots}}{\text{Total area of job}}$$

$P_j$  = Tendered amount for each job

- .3 No payment will be made for a job if more than 50% of the lots are non-conforming. Payment for non-conforming lots can be claimed once the lots meet the acceptance criteria.